


Category 6A FTP Patch Cord

PRODUCT SPECIFICATION

Package includes:

A. CAT 6A FTP Patch Cord, 1 pc



Features and Benefits:

- Component rated CAT 6A patch cords assuring high signal quality, minimal cross talk and return loss, and minimizing alien crosstalk and unwanted emissions
- Creates a high speed CAT 6A connection for cross and direct connects by patching cable runs to subsystems and equipment
- Designed with a low profile snagless boots for high density applications without any compromise in performance
- Exceeds ANSI/TIA-568-C for Category 6A connecting requirements
- Available in 3, 5, 7, 10, 15, and 25 FT

PATCH CORD, CAT 6A, FTP

ITEM NO. SEE DETAIL ON PAGE 2

REV. B


DWG NO. PSPCSG0000

PAGE NO. 1



CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd, La Mirada, CA 90638 * Phone 562-356-3111 * Fax 562-356-3100 * www.icc.com

©2008 ICC. THIS DOCUMENT AND THE DESIGNS, SPECIFICATIONS AND INFORMATION CONTAINED HEREIN ARE THE PROPERTY OF ICC. REPRODUCTION, MODIFICATION, ALTERATION, OR UNAUTHORIZED USE WITHOUT ICC'S APPROVAL IS STRICTLY PROHIBITED. ICC AND THE ICC LOGO ARE THE TRADENAME AND REGISTERED TRADEMARK OF ICC. ALL RIGHTS RESERVED.



NOTES: UNLESS OTHERWISE SPECIFIED

1. CONSTRUCTION:

A. CONDUCTOR:

- 4 TWISTED PAIR: BLUE, ORANGE, GREEN, BROWN
- 26 AWG (STRANDED BARE COPPER 7X0.152mm)

B. INSULATORS: HDPE (MIN. THICKNESS 0.153

C. INSULATORS DIAMETER: 1.03±0.10MM

D. ALUMINUM FOIL: 50u X 12MM

E. DRAIN WIRE: 7 X 0.152MM

F. JACKET: 75°C PVC

G. JACKET DIAMETER: 0.248"±0.006 (6.3±0.15MM)

H. SHIELDED MODULAR PLUG: 8P8C

CONTACT: PHOSPHOR BRONZE, 50u" GOLD PLATED

INSULATOR: POLYCARBONATE, UL94V-2

COLOR: NATURAL

I. BOOT: PVC

2. ELECTRICAL:

A. VOLTAGE RATING: 300V

B. TEMPERATURE RATING: 75°C

C. DIELECTRIC STRENGTH: DC 2.5 KV/2 SEC. OR AC 1.75 KV/2 SEC

D. MUTUAL CAPACITANCE: 5.6 nF/100M NOMINAL

E. PAIR TO GROUND: 300pf/100M MAX

F. CONDUCTOR DC RESISTANCE: 14.2 OHMS/KM MAX AT 25°C

G. DC RESISTANCE UNBALANCE: 4% MAX.

H. CHARACTERISTIC IMPEDANCE: 100±15 OHMS 1~500MHz

I. PROPAGATION DELAY SKEW: 50ns/100M MAX. 1~500MHz

J. VELOCITY OF PROPAGATION: 70%

3. MECHANICAL:

A. TENSILE STRENGTH: POLYOLEFIN 2400PSI, JACKET (PVC) 2000PSI

B. ELONGATION: POLYOLEFIN 300% MIN, JACKET (PVC) 100%MIN

4. STANDARDS:

A. ANSI/TIA-568-C (500 MHz)

B. ISO/IEC 61156-6

C. FLAME RATING: UL 444, CMH, CMX, CM, CMG, CMR, FT4

5. APPLICATION:

A. 10GBASE-T (IEEE 802.3an)

1000BASE-TX (TIA/EIA-854)

1000BASE-T (IEEE 802.3ab)

100BASE-TX (IEEE 802.3u)

10BASE-T (IEEE 802.3)

6. COLORS: XX: BK-BLACK, BL-BLUE, YL-YELLOW, WH-WHITE

WIRING DIAGRAM		
PLUG A	PLUG B	COLOR
1	1	WHITE/ORANGE
2	2	*ORANGE
3	3	WHITE/GREEN
4	4	*BLUE
5	5	WHITE/BLUE
6	6	*GREEN
7	7	WHITE/BROWN
8	8	*BROWN

* A WHITE MARKING IS OPTIONAL

ITEM NO.	L(FT)	TOLERANCE(IN)
ICPCSG03XX	3	±1"
ICPCSG05XX	5	±1"
ICPCSG07XX	7	±1"
ICPCSG10XX	10	±1.5"
ICPCSG15XX	15	±1.5"
ICPCSG25XX	25	±1.5"

PATCH CORD, CAT 6A, FTP

ITEM NO. SEE DETAIL ABOVE

REV. B

DWG NO. PSPCSG0000

PAGE NO. 2



CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * Phone 562-356-3111 * Fax 562-356-3100 * www.icc.com