

D815 Desk Phone



Key Features

- 5" (480x272) color LCD
- 10 (36) configurable self-labeling multicolor LED keys
- 2 USB ports
- Elegant design
- WLAN
- Electronic Hook Switch (EHS)¹ support for wireless headsets
- D8C Expansion Module¹ ready
- 2-port Gigabit Ethernet switch (RJ45)
- 3-year standard warranty



Power over Ethernet



Self-Labeling Keys



USB Port



3 Year Warranty



HD Audio



Security (TLS & SRTP)



Headset Compatible



Expansion Module Ready



OpenVPN



IPv6 & IPv4

Phone Features

- 12 SIP identities / accounts
- XML browser
- Call lists for dialed, received, missed calls
- Local directory with 1000 entries
- Multiple language support
- DTMF in-band / out-of-band / SIP-INFO
- Interoperable with all major IP PBX platforms
- Speed dialing
- URL dialing
- Local dial plan
- Automatic redial on busy
- Call completion (busy / unreachable)²
- Caller identification
- Call waiting
- Call blocking (deny list)
- Auto answer
- Hold
- Music on hold²
- Blind and attended transfer
- Call forwarding
- 3-way conferencing on the phone
- Extension monitoring, call pickup²
- Call park, call unpark²
- Multicast paging
- DND mode (do not disturb)
- Keyboard lock
- Client matter code (CMC)²

Audio/Codexcs

- G.711 A-law, u-law
- G.722 (wideband)
- G.726, G.729ab, GSM 6.10 (FR)
- Built-in assignable ringtones
- Comfort noise generator (CNG)
- Voice activity detection (VAD)

Setup

- Configurable through web interface

Provisioning

- Automatic loading of settings via HTTP / HTTPS / TFTP
- DHCP Options 66/67
- Secure Redirection and Provisioning Service (SRAPS) support
- Remote management via TR-069 / TR-111

Protocols

- SIP (RFC3261)
- DHCP, NTP
- HTTP / HTTPS / TFTP
- LDAP (Directory)
- Dual Stack IPv4 / IPv6

User Interface

- Localization (language, time, dial tone)
- Red LED for call indication / message waiting
- 4 context sensitive keys
- 10 programmable line / function keys with multicolor LEDs
- Dedicated keys for: Message, directory, call history, transfer, hold, conference
- Audio keys with LED indication: Mute, speakerphone, headset
- Volume key
- 5-way navigation key
- Cancel key
- Menu-driven user interface

Security

- 802.1X Authentication and EAPOL
- Transport layer security (TLS)
- SRTP (RFC3711), SIPS, RTCP
- HTTPS server / client
- Password-protected web interface
- VPN support
- VLAN (IEEE 802.1Q)
- LLDP-MED, RTCP-XR

Specifications, Weight & Dimensions

Dimensions (Approximately)

- Without foot stand: 9.57" x 8.27" x 3.23"
- With desk stand: 9.57" x 6.8" x 7"

Weight (Approximately)

- 2.3 lbs
- Input voltage: 5V DC (SELV)
- Power supply: PoE or 5Vdc power adapter¹, 10 Watts
- Handset: 4P4C
- Headset: 4P4C; Support for Snom EHS Advanced¹
- Hearing aid compatible (HAC) handset
- 2 USB 2.0 host ports, Type A, Hi / Full / Low-speed
- 2 RJ45-8P8C Gigabit Ethernet port
- WLAN IEEE 802.11n/ac

Environmental Conditions

- Ambient temperature: 0°C to 35°C (32°F to 95°F)
- Storage temperature: -10°C to 45°C (14°F to 113°F)
- Humidity: 5% to 95% (non-condensing)

Included in Delivery

- Phone unit
- Foot stand
- Handset with cord
- Ethernet cable
- Quick Start Guide
- Color: Gunmetal Black
- Warranty: 3 years
- D815 APN: 80-S212-00

APN # for Optional Accessories

- D8C Expansion Module (Black): 80-S127-00
- Power Adaptor Snom A6 / US Clip: 26-350200-3UL
- Snom EHS Advanced: 89-S015-00
- A100D Binaural Headset: 89-S020-00
- A100M Mono Headset: 89-S019-00
- A230 DECT USB Stick: 80-S050-00
- A330M Mono USB Headset: 80-S149-00
- A330D Binaural USB Headset: 80-S150-00

- 1 - Optional accessory
- 2 - If supported by PBX