

FEATURES:

- UTILIZES STANDARD CAT 3, 5, OR 6 CABLE
- EXCELLENT VOICE AND MUSIC REPRODUCTION
- BUILT-IN ACCESSIBLE VOLUME CONTROL
- WIDE SOUND DISPERSION
- ELECTRICALLY, ACOUSTICALLY MATCHED COMPONENTS
- STURDY STEEL GRILLE
- ADDITIONAL POP-ON, POP-OFF KNOB INCLUDED

**DESCRIPTION:**

Square flush mount 11.5" speaker assembly, complete with speaker, amplifier, built-in volume control and square grille.

Specifications:

SPEAKER ELEMENT Cone Diameter: 8" (20.32 cm) Voice Coil Impedance: 45 Ohms	ENVIRONMENT Temperature: -4 ° to +131 °F (-20 to +55 °C) Humidity: 0-95% Non-Condensing
INPUTS Impedance: > 600 Ohms nominal Signal Level : -15dBm line level	HOUSING AND FINISH Steel grille finished in semi-gloss white enamel.
OUTPUT Rating: > 96 dB @ 4' (1.22 m) Signal/Noise Ratio: -70	DIMENSIONS AND WEIGHT 11.5 "Lx 11.5 "W x 3.0 "D (29.21 cm x 29.21 cm x 7.62 cm) Weight: 2.6 lbs (1.17 kg) Shipping Weight: 3.5 lbs (1.575 kg)
FREQUENCY RESPONSE 80 Hz to 15 kHz	OPTIONAL MOUNTING ACCESSORIES V-1991 Square Surface Mount Backbox (Metal) V-1992 Square Flush Mount Backbox (Metal)
POWER REQUIREMENTS 50 mA @ -24 Vdc	



Technical Specification

AMPLIFIED SPEAKER MODEL V-1920C

ARCHITECTS' AND ENGINEERS

The flush mounted 11.5" amplified speaker, Model V-1920C, shall include a speaker, amplifier, volume control and square grille. The speaker assembly, amplifier module, housing and hardware shall be electrically and acoustically matched for a frequency response of 80 Hz to 15 kHz.

The speaker element shall be cone type with 5 oz (142 g) ceramic magnet. Diameter of speaker cone shall be 8.0" (20.32 cm). Voice coil diameter shall be .75" (1.91 cm). Voice coil impedance shall be 45 ohms.

The amplifier shall have a frequency response of 80 Hz to 15 kHz. Distortion shall be less than 1.5% at rated output of 1 watt RMS. Signal to noise ratio shall be -70 dB. The amplifier shall operate on a -24 Vdc nominal power supply. Operating current shall be 50 mA at -24 Vdc. Operating temperature shall be -4 to +131 °F (-20 to +55 °C).

A screwdriver adjustable volume control shall be provided at the center of the grille. The externally accessible volume control shall make it possible to adjust volume level of speaker without removal of unit. A plastic pop off knob for volume control is included. The grille shall be constructed of steel, finished in semi-gloss white enamel. The maximum dimensions shall be: Speaker and Grille - 11.5 "Lx 11.5 "W x 3.0 "D (29.21 cm x 29.21 cm x 7.62 cm). Shipping Weight shall be approximately: Speaker and Grille: 2.6 lbs (1.17 kg).

Limited Warranty

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the re-placement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened (A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (major repairs will be subject to additional charges for parts and labor)

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.