AUDIO CABLE
16 AWG / 2 Conductor

Description

16/2 Stranded CMR/CL3R Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 2 Oxygen Free Bare Copper Conductors in an Overall Jacket

Physical Characteristics

Conductor		**Oxygen Free B.C.**
Number of Conductors		2
AWG		16
Stranding		65
Diameter	(inches)	0.0063
Insulation		**PVC**
Diameter	(inches)	0.0827
Average Thickness	(inches)	0.0122
Min. Point Thickness	(inches)	0.0106
Assembly Diameter	(inches)	0.1614
Jacket		**PVC**
Outer Diameter	(inches)	0.2008
Average Thickness	(inches)	0.0197
Min. Point Thickness	(inches)	0.0177
Rip Cord		**Nylon**
Conductor Resistance	(ohms)	**15.5**
Nominal Weight	(pounds)	**15**
Voltage Rating	(volts)	**300v**

Colors

Insulation Colors	**Black / Red**

Part Numbers

Part Number	Color		Put-up
AC1602RBK4-500	Black	500'	Reelex II
AC1602RWH4-500	White	500'	Reelex II

Cable Marking

AUDIO CABLE 2 COND 16AWG HI-STRAND OFC CMR/CL3R FT4 75C XXXXXX C(ETL)US ****FT

www.wavenet.net Toll. 888-492-8363 Tel. 310-885-4200 707 E. Sepulveda Blvd., Carson, CA 90745