
6P4C Line Cord, Pin 2-5

PRODUCT SPECIFICATION

Package includes:

A.6P4C Line Cord, 1 pc




Features and Benefits:

- Flat 6P4C line cord designed for all voice connectivity applications
- Used with IC1076 voice modules, IC107C6 6P6C RJ-11 coupler modules, and/or ICMA267, ICMA350 6P6C modular couplers
- Available in 7, 14, and 25 FT
- Available in silver satin
- ANSI/TIA-568-C and UL 1863 compliant

LINE CORD, 6P4C, PIN 2-5					
ITEM NO.	ICLC4XXFSV	REV. B			
DWG NO.	PSLC400FSV	PAGE NO.	1		



CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 2100 E. Valencia Dr, Suite D, Fullerton, CA 92831 * www.icc.com



NOTE: UNLESS OTHERWISE SPECIFIED

1. ELECTRICAL/PHYSICAL:

- A. TELEPHONE CORD:
 - -RESISTANCE OF CONDUCTOR: 148 OHMS/KM MAX AT 20¢XC
 - -RESISTANCE OF INSULATION: 100 MOHMS/KM MIN AT 20¢XC
 - -DIELECTRIC WITHSTANDING VOLTAGE: 500 VOLTS AC
 - -TEMPERATURE AND VOLTAGE RATING: 60¢XC, 150V
- B. MODULAR PLUG:
 - -UL APPLICATIONS: 250 VOLTS AC MAX, AT 2 AMPS MAX
 - -RESISTANCE OF INSULATION: 500 MOHMS
 - -RESISTANCE OF TERMINATION: 35 MILLIOHMS MAX AFTER 20¢XC
 - -DIELECTRIC WITHSTANDING VOLTAGE: 500 VOLTS AC
- 2 MECHANICAL:
 - A. CABLE-TO-PLUG TENSILE STRENGTH: 20 LBS [89N] MIN
 - B. DURABILITY: 200 MATING CYCLES MIN
- 3 MATERIAL & FINISH:
 - A. TELEPHONE CORD: UL STYLE 20251, CSA II A/B
 - -JACKET
 - MATERIAL: FR-PVC, FLAT
 - OVERALL DIAMETER: 0.0945"x0.2756"¡Ó0.00394"
 - AVERAGE THICKNESS: 0.0200" MINIMUM THICKNESS: 0.0162"
 - -INSULATION:
 - MATERIAL: PP
 - OVERALL DIAMETER: 0.0374"¡Ó0.00197"
 - AVERAGE THICKNESS: 0.0071" MINIMUM THICKNESS: 0.00512"
 - -CONDUCTOR: 26 AWG (7X34) COPPER WIRE, STRANDED
 - B. MODULAR PLUG: UL AND cUL RECOGNIZED
 - -HOUSING: PC, UL 94V-2
 - -COLOR: CLEAR
 - -CONTACT: HIGH STRENGTH COPPER ALLOY
 - GOLD PLATING OVER 100 MICRO INCH NICKEL
 - -GOLD PLATING: 1,27 MICRONS/50 MICRO INCH MIN ON CONTACTS
 - -NO. OF CONTACTS: 4
- 4. LENGTH: XX: 07-7 FT, 14-14 FT, & 25-25 FT

WIRING DIAGRAM:

PLUG A	PLUG B	COLOR
2	5	BLACK
3	4	RED
4	3	GREEN
5	2	YELLOW

ITEM NO.	LENGTH
ICLC407FSV	7' ± 1.0"
ICLC414FSV	14' ± 1.5"
ICLC425FSV	25' ± 2.0"



LINE CORD, 6P4C, PIN 2-5				
ITEM NO.	ICLC4XXFSV	REV. B		
DWG NO.	PSLC400FSV	PAGE NO. 2		



CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 2100 E. Valencia Dr, Suite D, Fullerton, CA 92831 * www.icc.com