

# SurgeGate™ Modular Rack Mount

**SurgeGate**  
*Enduring Surge Protection*



## Features:

- UL Listed for Primary (497) and Isolated Loop (497B) applications
- Exceeds TIA/EIA Standards 568 and 758 for CAT 5e performance
- Solid-state protection provides the fastest response to transient voltages (1-5 nanoseconds) by quickly diverting damaging surges to ground
- Use between buildings in a campus environment as a building entrance protector or in hostile industrial applications as an isolated loop protector
- Up to 12 individual and replaceable port modules
- RJ45 input to RJ45 output
- Single-height rack mountable chassis (1U)

**ITW Linx®**  
*Surge Protection Solutions*



Tel: 630.315.2150  
Fax: 630.315.2152

[www.itwlinx.com](http://www.itwlinx.com)

# SurgeGate

Enduring Surge Protection

For up-to-date warranty information, please visit our web site at [www.itwlinx.com](http://www.itwlinx.com)



## TECHNICAL SPECIFICATIONS

### PRODUCT SPECIFICATIONS:

Agency Approval	UL Primary (497) and Isolated Loop (497B)
Grounding Requirements	Field installed solid copper wire #6 AWG for Primary #14 AWG for isolated Loop
Recommended Grounding Impedance	<0.5 Ohm
Width	19"
Height	1.7"
Depth	4.0"
Weight w/o Modules	2.9lbs
Product Warranty	Lifetime
Connected Equipment Warranty	Up to \$5,000

### SINGLE LINE SURGE PROTECTION: (LAN)

Signal Perfect Circuitry	Yes
Fused	No
Performance Rating	CAT5e / Gigabit Ethernet
Clamping Level	CAT5e-LAN = 16V CAT5e-75/POE = 75V CAT5e-235 = 235V
Response Time	T1 = 235V
Capacitance	Telco/CO = 235V
Wires Protected	1-5 Nanoseconds
Termination Type	< 20pF 8-wires, 4-pairs per port RJ - 45 In and Out

### ORDERING INFORMATION

Part Number	Description
RM-M12PVD	Modular Rack - up to 12 individual protection modules
RM12-CAT5-LAN	Protection Module, Solid State CAT5-LAN application with 16 volts clamping voltage
RM12-CAT5-75/POE	Protection Module, Solid State CAT5 with 75 clamping voltage for digital/POE applications
RM12-CAT5-235	Protection Module, Solid State CAT5 with 235 clamping voltage for T1, Telco and analog lines

\*Questions about ordering? Please contact us at 1-800-336-linx / Contact an authorized distributor for pricing\* (MOQ:6)