

DESKTOP/WALL ONE-WAY SPEAKER MODEL V-763

FEATURES:

UTILIZES STANDARD CAT 3, 5, OR 6 CABLE

SITS ON DESKTOP OR MOUNTS ON WALL

EXTERNALLY ACCESSIBLE VOLUME CONTROL

ATTRACTIVE WHITE, GRAY OR BLACK FINISH



DESCRIPTION:

Desktop or wall surface mounted speaker assembly complete with speaker, amplifier and built-in volume control.

SPECIFICATIONS:

FREQUENCY RESPONSE

220 Hz to 10 kHz

INPUT

Impedance: 600 Ohms nominal

Signal Level: -10 dBm line level

OUTPUT

Rating: ≥ 93 dB @ 4' (1.22 m)

POWER REQUIREMENTS

50 mA @ -24 Vdc

HOUSING AND FINISH

Available in Black, Gray or White.

DIMENSIONS AND WEIGHT

3.9" (9.91 cm) H x 5.1" (12.95 cm) W x 3.2" (8.13cm) D

Weight: 0.6 lbs (0.27 kg)

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

MODEL V-763

DESKTOP/WALL ONE-WAY SPEAKER

The Desktop/Wall Speaker, Model V-763 shall consist of a 45 ohm speaker, amplifier with 600 ohm input impedance and volume control. The speaker, housing and hardware shall be electrically and acoustically matched for a frequency response of 220 Hz to 10kHz.

The speaker element shall be cone type. Voice coil impedance shall be 45 ohm.

The amplifier shall have a frequency response of 220 Hz to 10 kHz. Amplifier audio input impedance shall be ≥ 600 ohm. Amplifier audio input shall be -10 dBm line level. The amplifier shall operate on a -24 Vdc nominal, positive ground power supply. Operating current shall be 50 mA at -24 Vdc.

A volume control shall be provided on the unit. This volume control shall be externally accessible, making it possible to adjust volume level of speaker without tools.

The V-763 shall be available in black, gray or white.

Maximum dimensions of the housing shall be 3.9" (9.91 cm) H x 5.1" (12.95 cm) W x 3.2" (8.13cm) D. Approximate weight is 0.6 lbs (0.27 kg).

Limited Warranty

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened.
(A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs
(major repairs will be subject to additional charges for parts and labor).

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.